

## TECHNICAL DATA

# Geocel® Plumbers Putty

## Non-setting putty for sanitary joints



Geocel® Plumbers Putty is a ready mixed and ready to use permanently flexible, non-setting joint sealant formulated for general use. It is ideal for sealing sanitary joints, guttering and down pipes, and for bedding in sinks and vanity units.

Geocel® Plumbers Putty is easy to use and has good adhesion properties to a wide variety of substrates including metal, PVC, vitreous enamels and ceramics. It can also be overpainted and is compatible with most common cleaning fluids.

- Fast, easy and safe to use
- Permanently flexible
- Watertight
- Non-cracking
- Can be overpainted

### PRINCIPAL APPLICATIONS

Geocel® Plumbers Putty is ideal for:-

- Sealing spigot and socket joints
- Use on guttering and downpipes
- Bedding in of sinks and vanity unit
- Sanitary joints subject to vibration or a small degree of movement
- Bedding waste grills in sinks and basins
- Providing a seepage seal in non-pressurised situations
- Many other uses around the home, boat or caravan

### TECHNICAL DATA

<b>Form</b>	Smooth air free paste
<b>Storage Life</b>	12 months in original containers stored between 5°C and 23°C
<b>Colour</b>	Light beige

**Specification writers:** These values are not intended for use in preparing specifications. Please contact your local Geocel® Sales Representative prior to writing specifications on this product.

### SURFACE PREPARATION

Ensure that all surfaces are clean, sound and free from grease. Wipe with a clean cloth followed by a final wipe with a small piece of Geocel® Plumbers Putty.

### APPLICATION

To seal spigot and socket joints: Assemble joint, ensuring the spigot is correctly positioned. Tightly pack back of the joint with untarred hemp. Press Geocel® Plumbers Putty firmly into the joint until the void is completely filled. Smooth off to give a professional finish.

Used as a bedding mastic: Apply even bead of Geocel® Plumbers Putty to one component, position and secure second component.

### CLEANING

Remove excess Geocel® Plumbers Putty from surfaces with a putty knife or by rubbing off with another piece of putty.

### PACKAGING

Geocel® Plumbers Putty is available in 750g tubs packed in boxes of 12.

### HEALTH AND SAFETY

Health and Safety data sheets available on request.

### TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Geocel® Technical Service.

**Important Note:** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages.