

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY**

- 1.1 Product name** : DOW CORNING(R) FIRESTOP 800 SEALANT GREY
- 1.2 Identified uses** : Construction materials and additives
- Uses advised against** : None known.
- 1.3 Company** : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe
Belgium
- E-mail address (Safety Data Sheet)** : sdseu@dowcorning.com
- Customer Service** : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163
- Fax: +32 64888683
- 1.4 Emergency Phone Number** : Dow Corning (Barry U.K. 24h) Tel: +44 1446732350
Dow Corning (Wiesbaden 24h) Tel: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

According to EU Directives 67/548/EEC or 1999/45/EC:

Not hazardous.

2.2 Label elements**Labelling according to EEC Directive**

- S-phrases** : S24 Avoid contact with skin.
S51 Use only in well-ventilated areas.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer**According to EU Directives 67/548/EEC or 1999/45/EC:**

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Calcium carbonate	471-34-1	207-439-9	01-21194867 95-18	36.0	Substance with a Community workplace exposure limit
N,N'-(Vinylsilylene)bis(N-methylacetamide)	50791-87-2	256-766-3	-	2.3	Xi R41 Xn, Toxic for reproduction - category 3. R63 R52/53
Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine	68952-53-4	Exempt or not available	-	1.4	Xi R36/38
N-Methylacetamide	79-16-3	201-182-6	-	0.11	T, Toxic for reproduction - category 2. R61

According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Calcium carbonate	471-34-1	207-439-9	01-21194867 95-18	36.0	Substance with a Community workplace exposure limit
N,N'-(Vinylsilylene)bis(N-methylacetamide)	50791-87-2	256-766-3	-	2.3	Serious eye damage/eye irritation: Category 1 - H318 Reproductive toxicity: Category 2 - H361d Chronic aquatic hazard: Category 3 - H412
Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine	68952-53-4	Exempt or not available	-	1.4	Skin corrosion/irritation: Category 2 - H315 Serious eye damage/eye irritation: Category 2 - H319
N-Methylacetamide	79-16-3	201-182-6	-	0.11	Reproductive toxicity: Category 1B - H360D

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

4. FIRST AID MEASURES**4.1 Description of First Aid Measures:**

- On contact with eyes** : Flush with water. If eye irritation persists, get medical attention.
- On skin contact** : Flush with water.
- If inhaled** : Remove to fresh air.
- On ingestion** : No first aid should be needed.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media** : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- 5.2 Hazards during fire fighting** : None known.
- Hazardous Combustion Products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Quartz. Nitrogen products. Chlorine compounds.
- 5.3 Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** : Wear proper protective equipment.
- 6.2 Environmental precautions** : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
- 6.3 Methods and materials for containment and cleaning up** : Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0
 Revision Date: 06.03.2013
 Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY

an extremely slippery surface.

7. HANDLING AND STORAGE

- 7.1 Advice on safe handling** : General ventilation is recommended. Local ventilation is recommended. Do not breathe vapour. Do not breathe spray or mist. Avoid eye contact. Do not empty into drains.
- 7.2 Advice on storage** : Do not store with oxidizing agents.
 Storage temperature: minimum -18 °C, maximum 32 °C
- 7.3 Specific uses** : Refer to technical data sheet available on request.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Name	CAS-No.	Exposure Limits
Calcium carbonate	471-34-1	4 mg/m ³ TWA Respirable dust 10 mg/m ³ TWA Inhalable dust
N,N'-(Vinylsilylene)bis(N-methylacetamide)	50791-87-2	1 ppm 8h TWA, 5ppm STEL-C Dow Corning recommendation.
N-Methylacetamide	79-16-3	1 ppm 8h TWA, 5ppm STEL-C Dow Corning recommendation.

8.2 Exposure controls

Engineering Controls : Ventilation : Refer to Section 7.1

Personal protection equipment

Respiratory protection : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
 A suitable respirator must be worn if the product is used in any circumstances where an aerosol or mist may be generated, such as during spraying or similar activities.
 Depending on the working conditions, wear a respiratory mask with filter(s) AXP or use a self-contained respirator.
 The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.

Hand protection : Gloves are not normally required.

Eye/face protection : Safety goggles should be worn.

Skin protection : Protective equipment is not normally necessary.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY

Hygiene measures	:	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
Additional information	:	These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.
<u>Environmental exposure controls</u>	:	Refer to section 6 and 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	:	Liquid
Colour	:	Charcoal
Odour	:	Fishy
Boiling point/range	:	> 35 °C
Flash point	:	100 °C (Pensky-Martens Closed Cup)
Explosive properties	:	No
Specific Gravity	:	1.3
Viscosity	:	300000 cSt at 25°C.
Oxidizing properties	:	No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

10.1 Reactivity	:	None known.
10.2 Stability	:	Stable under normal usage conditions.
10.3 Possibility of hazardous reactions	:	None known.
10.4 Conditions to avoid	:	None established.
10.5 Materials to avoid	:	Can react with strong oxidising agents.
10.6 Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Quartz. Nitrogen products. Chlorine compounds.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY**11. TOXICOLOGICAL INFORMATION****Acute toxicity:**

- On contact with eyes** : Slightly irritating.
- On skin contact** : Slightly irritating.
- If inhaled** : The vapour is irritating to the mouth, nose and throat.
- On ingestion** : No adverse effects are normally expected.

Chronic toxicity:

- On skin contact** : Can irritate on prolonged or repeated skin contact.
- If inhaled** : Prolonged or repeated inhalation may cause irritation of the upper respiratory system.
- On ingestion** : No adverse effects are normally expected.

Toxicokinetics, metabolism and distribution : No specific information is available.

Other Health Hazard Information : This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity effects**

No adverse effects on aquatic organisms.

12.2 Persistence and degradability

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.3 Bioaccumulation

No bioaccumulation potential.

12.4 Release to waters / Mobility in soil**Fate and effects in waste water treatment plants:**

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY

not contribute to the BOD.

13. DISPOSAL CONSIDERATIONS

Product and packaging disposal : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION**Road / Rail (ADR/RID)**

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Status**

EINECS : All ingredients listed, exempt or notified (ELINCS).

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

AICS : All ingredients listed, exempt or notified.

IECSC : All ingredients listed or exempt.

KECL : All ingredients listed, exempt or notified.

PICCS : All ingredients listed, exempt or notified.

DSL : All ingredients listed or exempt.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 06.03.2013

Superseded date: 23.01.2012

DOW CORNING(R) FIRESTOP 800 SEALANT GREY**16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

R36/38 Irritating to eyes and skin., **R41** Risk of serious damage to eyes., **R52/53** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment., **R61** May cause harm to the unborn child., **R63** Possible risk of harm to the unborn child.

H315 Causes skin irritation., **H318** Causes serious eye damage., **H319** Causes serious eye irritation., **H360D** May damage the unborn child., **H361d** Suspected of damaging the unborn child., **H412** Harmful to aquatic life with long lasting effects.