



Version 1

## DECLARATION OF PERFORMANCE

### **No SNF\_DOP\_002**

1. Unique identification code of the product-type:

#### **Dow Corning® 993 Structural Glazing**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Effective from 30 June 2013**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

#### **Insulating glazing sealant for use in structural sealant glazing systems**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Dow Corning Europe S.A.**  
**1 rue Jules Bordet, parc industriel zone C**  
**7180 Seneffe, Belgium**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 1+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**N/A**

(name and identification number of the notified body, if relevant)

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Ubatc**

(name and identification number of the Technical Assessment Body, if relevant)

issued :

**BCCA 0749**

(reference number of the European Technical Assessment)  
on the basis of

**ETA 01/0005**

(reference number of the European Assessment Document)



Version 1

9. Declared performance

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
SPECIFIC MASS	1.33 (mixed ration 10:1)	ETAG last version
HARDNESS A	Mean of 36 Shore A	ETAG last version
DESIGN STRESS IN TENSION	0.14 MPa	ETAG last version
DESIGN STRESS IN DYNAMIC SHEAR	0.11 MPa	ETAG last version
DESIGN STRESS IN STATIC SHEAR	0.11 MPa	ETAG last version
ELASTIC MODULUS IN TENSION (E <sub>0</sub> )	1.4 MPa	ETAG last version
ELASTIC MODULUS IN SHEAR TANGENTIAL TO THE ORIGIN (G <sub>0</sub> )	0.47 MPa	ETAG last version
WORKING TIME (25°C, 50%RH)	10 - 30 min	ETAG last version
TACK FREE TIME (25°C, 50%RH)	80 - 100 min	ETAG last version
TIME BEFORE TRANSPORT OF THE BONDED FRAME	Min 10 days	ETAG last version
TENSILE STRENGTH, H-BAR (ALU-GL), 23°C-50RH + 1 d H <sub>2</sub> O	> 0.70 MPa	ETAG last version
COH. FAILURE 100%, H-BAR (ALU-GL), 23°C-50RH	100 %	ETAG last version

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

**Gregory Chambard**  
 (name)

**Science & technology Manager**  
 (Function)

Seneffe, June 30<sup>th</sup>, 2013

*The information contained herein is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Corning makes not warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.*