

Geocel® Lead & Gutter Silicone is a silicone rubber sealant for the installation and maintenance of gutter systems and downpipes, and for pointing joints between lead flashing and brickwork, masonry and stonework. It is a high-performance sealant that gives excellent adhesion to most common guttering systems including plastics, metals, painted surfaces and PVC-U.

Geocel® Lead & Gutter Silicone has a high joint movement capability and will give a totally water-resistant seal.

- No primer needed
- High movement capability
- Will not crack, shrink or craze
- Remains permanently flexible
- Weather resistant
- Maintenance free
- Long service life

APPLICATION

Ensure substrates, gaps and cracks are clean dry and free from dust, dirt and grease. Remove nozzle and cut off end of cartridge. Replace nozzle and cut tip to required width. Place the cartridge in a cartridge gun and apply material into substrate, gap and crack to be filled. Ensure **Geocel® Lead & Gutter Silicone** makes full contact with the sides and back of the joint.

LIMITATIONS

Geocel® Lead & Gutter Silicone should not be applied to building material that bleed oils, plasticisers, or solvents. Mis-applied material can be removed when uncured using white spirit. Cured material can be removed using Geocel Silicone Sealant remover. Do NOT apply sealant in wet conditions or if rain is imminent.

PACKAGING

Geocel® Lead & Gutter Silicone is available in cartridges packed in boxes of 12.

STORAGE LIFE

12 Months from date of manufacture when stored in unopened original packaging at room temperature.



SPECIFICATIONS

ISO 9001

ISO 14001

ISO 11600 – F&G 20 LM

TECHNICAL DATA

Colours	Black, Grey
Tack Free Time	30 minutes
Skin Time	20 Minutes
Cure Rate	3 mm after 24 hours
Application Temperature	5°C – 40°C
Service Temperature	-20°C – 140°C
Movement Accommodation Factor	25±
Shore A Hardness	25
Specific Gravity	1.18
Tensile Strength	1.46 Mpa
Elongation	1000%

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

HEALTH AND SAFETY

Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

Tel: 0114 240 9305

Email: technical@geocel.co.uk

IMPORTANT NOTE: The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damage.

Legal Note: Any reference to "Geocel" is to the brand Geocel which is owned and operated by Sherwin-Williams UK Limited

