



DECLARATION OF PERFORMANCE

No SNF_DOP_026

www.dowcorning.com
eutech.info@dowcorning.com

Version 1
Effective from: 30 Jan.2015

1. Unique identification code of the product-type:

Dow Corning® 896 PanelFix for Panel Bonding

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see product packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Silicone Adhesive for tiles: EN 12004: 2007 +A1/ 2012

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Dow Corning Europe S.A.
1 rue Jules Bordet, Parc Industriel zone C
7180 Seneffe, Belgium

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 4 for reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 12004: 2007 +A1/ 2012 and issued a test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

Disclaimer : The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Corning makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



9. Declared performance

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	UNE-EN-ISO 11925-2:2011
Release of Chemicals	None	See product safety data sheet
Water Tightness & Air Tightness as determined by :		
Initial Shear adhesion strength	>2MPa	EN 12004 : 2007 +A1/ 2012
Open time	>0.5MPa after not less than 20min	
Shear adhesion after water immersion	>2MPa	
Shear adhesion after heat ageing	>2MPa	
Shear adhesion at 70C	>2MPa	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Loriane Parisot

High Performance Building AETS manager EMEA

Seneffe, 30 Jan 2015