

DECLARATION OF PERFORMANCE

No.SNF_DOP_001.....

1. Unique identification code of the product-type:895....

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Effective from 30 June 2013

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
 sealants used in structural sealants glazing systems to bond glass onto metal.....

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Dow Corning Europe S.A.,.....
1 rue Jules Bordet, parc industriel zone C.....
7180 Seneffe, Belgium.....

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
N/A.....

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 1 +.....

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
N/A.....

(name and identification number of the notified body, if relevant) performed under system

(description of the third party tasks as set out in Annex V) and issued

..
 (certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
UBAtc.....

(name and identification number of the Technical Assessment Body, if relevant) issuedBCCA...0749.....

(reference number of the European Technical Assessment) on the basis ofETA 01/0005

(reference number of the European Assessment Document)

performedN/A..... under system

(description of the third party tasks as set out in Annex V) and issued

..
 (certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

9. Declared performance

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
SPECIFIC MASS	1.45	ETAG last version
HARDNESS A	Mean of 33 Shore A	ETAG last version
DESIGN STRESS IN TENSION	0.14 MPa	ETAG last version
DESIGN STRESS IN DYNAMIC	0.14 MPa	ETAG last version

SHEAR		
ELASTIC MODULUS IN TENSION (E ₀)	0.9 MPa	ETAG last version
ELASTIC MODULUS IN SHEAR TANGENTIAL TO THE ORIGIN (G ₀)	0.3 MPa	ETAG last version
WORKING TIME (25°C, 50%RH)	15 min	ETAG last version
SKIN OVER TIME (25°C, 50%RH)	15 min	ETAG last version
TACK FREE TIME (25°C, 50%RH)	30 – 50 min	ETAG last version
TIME BEFORE TRANSPORT OF THE BONDED FRAME	Min 21 days	ETAG last version
TENSILE STRENGTH, H-BAR (ALU-GL), 23°C-50RH + 1 d H2O	> 0.70 MPa	ETAG last version
COH. FAILURE 100%, H-BAR (ALU-GL), 23°C-50RH	100 %	ETAG last version

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

.....

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

.Gregory Chambard.....Science & Technology manager.....
 (name and function)

Saxeffe, 21-June-2013
 (place and date of issue) (signature)
