



DECLARATION OF PERFORMANCE

No SNF_DOP_010

1. Unique identification code of the product-type:

Dow Corning® 781 Acetoxy Silicone Sealant

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch Number: see product packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for Facade: EN-15651-1: F-EXT-INT-CC
Sealant for Glazing: EN-15651-2: G-CC

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Dow Corning Europe S.A.
1 rue Jules Bordet, Parc Industriel zone C
7180 Seneffe, Belgium

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3: System 3 for reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 15651-1; EN 15651-2 and reaction to fire system 3 and issued a test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant



9. Declared performance

Conditioning: Preparation A (According to ISO 8340)

Substrate: Glass (without primer) and Aluminium (with and without primer Dow Corning OS 1200)

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	
Release of Chemicals	None	See product safety data sheet
Water Tightness & Air Tightness as determined by :		
Resistance to flow	≤3mm	EN 15651-1,2
Loss of volume	≤10%	EN 15651-1,2
Adhesion/Cohesion at maintained extension after immersion in water	No Failure	EN 15651-1
Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	No Failure	EN 15651-1,2
Adhesion/Cohesion properties after exposure to heat water and artificial light	Pass Glass	EN 15651-2
Elastic recovery	≥60%	EN 15651-2
Durability	Pass	EN 15651-1,2

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Loriane Parisot
 High Performance Building AETS manager EMEA

Seneffe, 3rd February 2014